

Silicone Free Defoamer DCA-4532

 dcachem.com/portfolio/silicone-free-defoamer-dca-4532

Introduction

DCA-4532 is a non-silicone defoamer, especially suitable for saturated polyester, unsaturated polyester, epoxy, UV-curing systems, with excellent compatibility and defoaming properties.

Physicochemical Data

- Chemical composition: Non-silicone polymer
- Appearance: Light yellow transparent liquid
- Active content: 50%
- Solvent: Hydrocarbon solvent

Product features

- Excellent compatibility
- Excellent defoaming capability
- Good recoatability

Application areas

Suitable for saturated polyester, unsaturated polyester, epoxy, UV-curing systems, and more.

Addition Method

For a total amount of 0.3% to 1.0%, please conduct testing to determine the optimal dosage. Add the defoamer under sufficient shear force, and it is recommended to add it before grinding.

The dosage may vary depending on the specific system, and it can be added at any stage of production.

Packaging and storage:

25KG plastic drum, stored in a cool and dry place.

Note: The purpose of this manual is to provide basic product information to technical personnel involved in the development of coatings, inks, pesticides, and other industries. It is intended for research and reference use and does not carry any warranties. Please conduct preliminary tests to assess its suitability.

If there are some products you are interested or you have something need us to support,