

Silicone Antifoam DCA-4092



dcachem.com/portfolio/silicone-antifoam-dca-4092

Introduction

DCA-4092 is suitable for water-based systems and has strong defoaming and foam suppressing capabilities. It works well even at very low addition levels and is particularly suitable for eliminating microbubbles in high viscosity coatings and ink systems. As a self-emulsifying defoaming agent, it needs to be added during the grinding stage.

Physicochemical Data

- Chemical composition:Hydrophobic particle-modified polysiloxane
- Appearance:Light yellow turbid viscous liquid
- Active content: 100%
- Solvent: None

Product features

- Excellent defoaming capability
- Rapid elimination of bubbles
- Has extremely high defoaming efficiency and shows excellent performance even at very low addition levels

Application areas

Suitable for water-based coating systems, including but not limited to the following application areas:

- Water based coating
- Water based ink

Similar Products: BYK-022

Our products have a good cost-performance ratio, receiving positive feedback from customers in China and overseas markets.

Addition Method

Generally, the dosage is 0.05-2% of the total amount, and it should be added to the system during the grinding stage. After adding, it should be stirred as much as possible to achieve good dispersion.

Packaging and storage:

25KG iron drum, stored in a cool and dry place.

If there are some products you are interested or you have something need us to support,

Just click the button.

[Ask for sample](#)[Ask for sample](#)
[Download DCA-4092](#)